

FEATURES

Dual Power Options

208/230V 1 PH or 3 PH

Easily Accessible

Convenient access to burner, fuel lines, and electrical controls.

Air Management

This unit's high static blower allows for outlet ducting up to 200 feet.



FVO-750 **Shown with optional 20" outlet**

MODEL	FVO-750	FVNP-750
FUEL TYPE	OIL	DUAL FUEL - LP/NG
BTU/HR	750,000	750,000
CFM	7,000	7,000
POWER REQUIREMENTS	208/230V/1PH/50A OR 208/230V/3PH/30A	208/230V/1PH/50A OR 208/230V/3PH/30A
FUEL TANK CAPACITY* FUEL CONSUMPTION*	CONTACT US 5.2 GAL/HR	EXTERNAL NAT. GAS: 750 CFH PROP. LP: 8.2 GAL/HR
HEAT EXCHANGER	16 GAUGE 304 SS	16 GAUGE 304 SS
FAN CONTROL	VFD STANDARD	VFD STANDARD
IGNITION	DIRECT SPARK	DIRECT SPARK
AIR OUTLET DIA. AIR INLET DIA.	(2) x 16" OR (1) x 20" (2) x 16"	(2) x 16" OR (1) x 20" (2) x 16"
BURNER TECHNOLOGY	RIELLO BURNER	RIELLO BURNER
RETURN AIR	YES	YES
L x W x H	98" x 36" x 61"	98" x 36" x 61"
WEIGHT	1,390 LBS	1,390 LBS

