

DIRECT FIRED HEATERS

These thermostatically controlled heaters are ideal for tent events or construction applications as they create a comfortable environment and are quiet, efficient, as well as simple to set-up. Flexible ducting options allow for heat to be directed to specific areas.



THC-85P



THC-175DF



THC-355CDF

MODEL	THC-85P (PROPANE) THC-85N (NAT. GAS)	THC-175DF	THC-355CDF
FUEL TYPE	PROPANE OR NAT. GAS	DUAL FUEL	DUAL FUEL
BTU/HR	85,000	175,000	330,000
CFM	450	1,200	2,600
POWER REQUIREMENTS	115V/60HZ/1PH/15AMP	115V/60HZ/1PH/15AMP	115V/60HZ/1PH/15AMP
FUEL CONSUMPTION	0.89 GAL/HR (PROP.) 85 CFH (NAT. GAS)	1.88 GAL/HR (PROP.) 175 (NAT. GAS)	3.6 GAL/HR (PROP.) 330 (NAT. GAS)
IGNITION	DIRECT SPARK	DIRECT SPARK	DIRECT SPARK
THERMOSTAT	20' CORD FOR REMOTE LOCATION	20' CORD FOR REMOTE LOCATION	20' CORD FOR REMOTE LOCATION
L x W x H	31" x 22" x 27"	35" x 24" x 33"	47" x 32" x 42"
WEIGHT	122 LBS	164 LBS	345 LBS

